

ESPRIMO Mobile D9510

Mobile power for your requirements

Issue: August 2008

Fujitsu Siemens Computers is the leading European IT manufacturer. With a strategic focus on innovative mobility and the dynamic data center, we offer a unique range of products and services from notebooks and desktops to servers and IT infrastructure solutions. Famous German engineering and exceptional in-house quality testing capabilities in our test centers ensure extraordinary product quality and reliability across all product lines.

ESPRIMO Mobile D9510

Do you require constant access to your data and an ergonomic display? The ESPRIMO Mobile D9510 is ready for any challenge thanks to its state-of-the-art Intel® Centrino® 2 processor technology. The 15.4-inch display enable ergonomic working, whether you are in the office or travelling. Connectivity is ensured via a large number of interfaces and optional UMTS/HSDPA. With its new clear-line design the ESPRIMO Mobile D9510 fits perfectly into your office environment.

Ergonomic working

Relaxed easy working throughout the day.

- 15.4-inch WXGA or WXGA+ display, ergonomic keyboard with touchpad and optional touchstick

Maximum connectivity

High performance, connectivity and a selection of classic and new interfaces enable constant data access and high-level productivity.

- Intel® Centrino® 2 processor technology, parallel and serial interface, E-SATA and optional WLAN, Bluetooth, UMTS

Long-term availability

Suit your systems to your requirements, even during a long "roll-out" phase.

- Freely-configurable entry notebook with reliable product availability of 12 to 18 months

Great flexibility

The family concept offers standardized accessory components for the ESPRIMO Mobile U, M, D, X series.

- Standardized port replicator, power supply unit and modular bay for optical drive, second battery or second hard disk



Components

Processor	Intel® Core™2 Duo T9600 (2.8 GHz), 6 MB, 1066 MHz Intel® Core™2 Duo T9400 (2.53 GHz), 6 MB, 1066 MHz Intel® Core™2 Duo P8600 (2.4 GHz), 3 MB, 1066 MHz Intel® Core™2 Duo P8400 (2.26 GHz), 3 MB, 1066 MHz Intel® Celeron® 575 (2.0 GHz), 1 MB, 667 MHz
Memory modules	2 GB (1 x 2 GB, DDR3), 1066 MHz 1 GB (1 x 1 GB, DDR3), 1066 MHz
Hard disk drives (internal)	320 GB, 5400 rpm, SATA, 2.5 -inch S.M.A.R.T. 160 GB, 7200 rpm, SATA, 2.5 -inch S.M.A.R.T. 160 GB, 5400 rpm, SATA, 2.5 -inch S.M.A.R.T. 120 GB, 5400 rpm, SATA, 2.5 -inch S.M.A.R.T.
Hard disk notes	ShockSensor for HDD shock protection One Gigabyte equals one billion bytes, when referring to hard disk drive capacity Accessible capacity may vary, also depending on used software and tool
Display	15.4-inch TFT 1440 x 900 pixel (WXGA+) 15.4-inch TFT 1280 x 800 pixel (WXGA)
WLAN (optional)	Atheros Minicard b/g 802.11 b/g Intel® Wireless WiFi Link 5300 AGN 11/13ch
UMTS/HSUPA (optional)	Option GTM 382 (downlink 7.2, uplink 2.0)
Modular bay options	2nd battery 2nd hard disk drive DVD Super Multi Weight saver
Base unit	ESPRIMO Mobile D9510
General system information	
Chipset	Intel® GM45, ICH 9-M
BIOS features	BIOS based on Phoenix TrustedCore Notebook
Memory slots	2 DIMM (DDR3)
Turbo memory	Optional 4 GB
Supported capacity RAM (max.)	8 GB
Interfaces	
DC-in	1
Audio: line-in / microphone	1
Audio: line-out /headphone	1
Internal microphones	2
USB 2.0 total	4
VGA	1
Serial (RS-232)	1
LAN / Ethernet RJ-45	1
Parallel	1
IEEE 1394 (FireWire)	1
Modem RJ-11	Optional
Docking connector for Port Replicator	1
Kensington Lock support	1
Memory card slots	1
ExpressCard slots	1
PC Card slot (Type I/II)	1
SIM card slot	1
eSATA & USB combo	1
Wired communication	
Modem type	Optional: 56 K V.92 modem MDC1.5
LAN	Built-in 10/100/1000 MBit/s Intel® 82567LF
Wireless technologies	
Antennas	3 Dual band WLAN antennas, 2 UMTS antennas
WLAN notes	Import and usage according to country-specific regulations.
UMTS	Optional
Keyboard and pointing devices	
	86 keys, 19mm pitch, 2,7mm stroke TouchPad with two mouse buttons Second set of mouse buttons Application buttons
Multimedia	
Audio type	On board
Audio codec	Realtek ALC262
Audio features	Stereo speakers, Internal microphone (array)
Camera	Optional: Built-in ConfCamera, 1.3 megapixel, VGA camera
Graphics	
max. resolution external display	1920 x 1200 / true color / 85 Hz (tbd.)

Graphics	
Graphics brand name	Mobile Intel® GMA 4500M HD
Graphic features	DualView (Windows XP & Windows Vista)

Power supply	
AC adapter	20 V / 90 W (4.5A)
1st battery	Li-Ion battery 6-cell, 5200 mAh, 57 Wh
2nd battery	Li-Ion 6 cell, 3800 mAh, 41 Wh
Battery features	Dynamic charge supported (rapid charge)
Runtime 1st battery	up to 4 h (tbd)
Runtime 1st + 2nd battery	up to 6 h (tbd)
Battery notes	Battery life may vary depending on product model, configuration, applications, power management settings and features utilized. Battery recharge time depends on usage.

Dimensions / Weight / Environmental	
Operating ambient temperature	5 - 35 °C
Operating relative humidity	20 - 85 % (running)
Dimension without stand (W x D x H)	363 x 260 x 39 mm
Weight	2.7 kg
Weight notes	Weight may vary depending on actual configuration.

Operating system	
Operating system optional preinstalled	Microsoft® Windows Vista® Home Basic Microsoft® Windows Vista® Business 32bit TwinLoad Microsoft® Windows® XP Professional (DVD)
Operating system compatible	Microsoft® Windows® XP Professional
Operating system notes	Driver support for Microsoft Windows XP

Additional Software	
Additional software (preinstalled)	Adobe Acrobat Reader Camera EasyGuide online user documentation Nero Essentials (burning software) Norton Internet Security (incl. Firewall) on Drivers & Utilities DVD for Microsoft Windows XP Drivers & Utilities DVD (DUDVD) Toshiba Bluetooth Stack Mobile Software Suite: Application Button Utility Wireless Selector Utility ShockSensor Utility Fan Control Utility Power Saving Utility
Additional software (optional)	Windows Vista® recovery media Drivers & Utilities DVD (DUDVD) UMTS connection manager (optional with UMTS) DVD playback software

Manageability	
Manageability features	DeskUpdate Driver management DeskView Migrate (optional) DeskView Control (optional)
Manageability type	DeskView 10.x client management including:
DeskView features	On/Offline remote client management Detailed system inventory management and reports BIOS Management Remote power management System notifications Security Remote Control DeskView Helpdesk Integration WoL (Wake on LAN)
Supported standards	PXE BootP (made4you) WMI
Manageability link	http://www.fujitsu-siemens.com/solutions/it_infrastructure_solutions/manageability/featurefinder.html

Security	
Physical security	Kensington Lock support
System security	Optional: Trusted platform module (TPM 1.2) Symantec Norton Internet Security
User security	Hard disk password User and supervisor BIOS password Separate SmartCard Slot Optional: Integrated Fingerprint Sensor SystemLock 2 BIOS SmartCard Security

Germany	
Compliance link	https://sp.fujitsu-siemens.com/sites/certificates/default.aspx

Portreplicator interfaces (optional)	
DC-in	1
Power on switch	1
Headphones	1
Microphones	1

Portreplicator interfaces (optional)

USB 2.0 total	4
VGA	1
DVI	1, DVI-D Single Link
Serial (RS-232)	1
PS/2 (mouse / keyboard)	1
LAN / Ethernet RJ-45	1
Parallel	1
Kensington Lock support	2
eSATA	1

Information about environmental care, policies, programs and our Environmental guideline FSC03230:

<http://www.fujitsu-siemens.com/aboutus>

Take back and Recycling information:

<http://www.fujitsu-siemens.com/recycling>

All rights reserved, including intellectual property rights. Technical data subject to modifications and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded.

Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

For further information see http://www.fujitsu-siemens.com/terms_of_use.html
Copyright © Fujitsu Siemens Computers

Published by
Fujitsu Siemens Computers
<http://www.fujitsu-siemens.com/>